

2MP Fixed-focal Wi-Fi Bullet Network

Camera DH-F2C-LED-K



Series Overview

The Bullet Series, which is under the Dahua Wireless series, are cameras that are not only easy to install and operate, but also perform outstandingly and are cost-effective. They capture sharp, detailed images of scenes in high definition and offer powerful functions, such as AI human detection, to accurately trigger alarms. Information is also synchronously sent to your phone to keep you up-to-date. With its IP67 rating, these cameras are able to withstand harsh environments, making them highly suitable for use in small and medium-sized settings such as small-sized retail stores.



2MP Clear images with sharp details



SD Card Low-cost storage



DMSS App Easy to use



Al Human Detection Focuses on what matters and reduces false alarms



IP67 Protection Withstands harsh environments



Full-color Captures full-color details



H.265

Advanced H.265 compression technology



Upgrade Your Experience with DMSS

Dahua Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.







Specifications

Camera

Image Sensor Max. Resolution

Electronic Shutter Speed

Illumination Distance

Illuminator On/Off Control

Illuminator Number

Max. Aperture Field of View

Intelligence

Human Detection

Video & Audio

Video Compression

Video Frame Rate

Resolution

Video Bit Rate

Day/Night

1920 (H) × 1080 (V) Auto/Manual 1/3 s-1/100,000 s Up to 30 m (98.53 ft) Auto 2 (Warm light)

1/3" CMOS

F1.6 2.8 mm: H: 98°; V: 55°; D: 115° 3.6 mm: H: 78°; V: 41°; D: 94°

Support the classification and accurate detection of human

H.264B; H.264; H.264H; H.265

Main stream: 1920 × 1080@(1–25/30 fps) Sub stream: 640 × 480@(1–25/30 fps) *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.

1080p (1920 ×1080); 1280 × 960 (1280 × 960); 1280 × 720 (1280 × 720)

QR Code×1

information×1

H.264: 32kbps ~ 4096kbps H.265: 12kbps ~ 4096kbps Color/B/W

WDR Motion Detection Smart Illumination Image Rotation Built-in MIC Audio Compression Network Network Port Wi-Fi Storage Management Software

DWDR

OFF/ON (4 areas, rectangular)

Mobile Client

General

Power Supply Power Consumption Operating Temperature **Operating Humidity** Protection Casing Material

Product Dimensions

Net Weight

Yes 0°/180° None None RJ-45 (10/100 Base-T) IEEE 802.11b/g/n 2.4-2.4835 GHz, 2.4 G; EIRP≤20 dBm Micro SD card (support max. 256 GB) Smart PSS; DSS; DMSS iOS;Android 12 VDC Basic: 2 W (12 VDC) Max. (H.265+warm light intensity): 5.3 W (12 VDC) -40 °C to +60 °C (-40 °F to +140 °F) <95% IP67

131.0 mm × 78.4 mm × 97.2 mm (5.47" × 4.80" × 3.83") (L × W × H) 254.5 g (0.56 lb)

What's in the box

Tools:



Installation Position Map×1 Mounting Plate×1 Screw Package×1 Waterproof Connector x 1

Documents:

Power Adapter×1

Quick Start Guide×1 Legal and regulation

Power:

Metal + plastic